bltc®

eBEE

IPカメラ

無線制御照明システム
LED照明とIPカメラを融合させた

eBEE

= BT Light + Wi-Fi + IP Camera

◆ セキュリティ

◆ 録画映像の保存

◆ 360° 全景映像

eBEEシステムはIPカメラ機能つきで、多拠点を遠隔操作することもできます。

商店

eBEEはインタネットで異なる場所のモニタリングができます。

IPカメラライト

IPカメラランプやダウンライトは、録画保存、プッシュ通知、調光調色機能など対応できます。

ゲートウェイ

保存機能

Micro SD Card 対応

映像ダウンロード

360°

IPカメラ
A80

照明制御機能

調光調色

360°

IPカメラ
ダウンライト

センサー機能

照度センサー

PIRセンサー

120°

Wi-Fi IPカメラ
+ゲートウェイ

セキュリティ

赤外線暗視

双方向音声通信

保存機能	HD画質、Micro SD Cardと映像ダウンロード
センサー機能	照度や人の動きを感知する
照明制御機能	専用アプリで調光調色
セキュリティ	1. 独自開発したIPカメラを360°全景を対応する 2. スピーカーとマイク内蔵で通話・録音できる

ゲートウェイライトコントロール

Bluetoothコントローラ

Switch Type Controller

Voice Controller

19 Key Controller

Bluetoothセンサー

5V PIR & Light Sensor

12V PIR & Light Sensor

12V Microwave & Light Sensor

Wi-Fi/4G/5G

ゲートウェイ

Gateway Desk Type

Gateway Wire Type

IP Camera

IP Camera Downlight

Wi-Fi IP Camera +Gateway

※ Wi-Fi 経由でゲートウェイを最大24台接続可能
※ ゲートウェイ一台でデバイスを最大128台接続可能

DALI REPEATER

Bluetooth LEDランプ

Bulb

G45

Candle

A60

A70

Filament

Candle Filament

A60 Filament

G95 Filament

ST64 Filament

MR. AR. PAR

MR16

GU10

PAR38

BR

BR30

BR40

JC. Disk

JC Bi-Pin

GX53 75mm

GX53 90mm

GX53 90mm

Bluetooth LED照明器具


Downlight Adjustable

Downlight 9cm

Downlight 15cm

Step light 5in / 9in

T5 Batten 1ft / 2ft / 3ft / 4ft

Bluetooth電源ユニット


Driver 1CH 40W


Driver 2CH 40W

Bluetoothアダプタ

0-10V Adapter

12V 0-10V Adapter

LED Stripe Adapter (2A/CH)

LED Stripe Adapter (10A/CH)

Outdoor Relay

Bluetoothリピータ

Indoor Repeater

Outdoor Repeater

センサー	Voltage(V)	Power(W)	Mesh Range	Sensor Range
5V PIR & Light Sensor	5 DC	0.8	15m	3-5m
12V PIR & Light Sensor	12 AC/DC	0.8	15m	3-5m
12V Microwave + Light Sensor	12 AC/DC	0.8	15m	5-10m



コントローラ	Voltage(V)	Power(W)	Mesh Range	Voice Range
Switch Type Controller	CR2450	0.3	15m	-
19 KEY Controller	AAA X2	0.3	15m	-
Voice Controller	5 DC	0.5	15m	3-5m



アダプタ	Voltage(V)	Max Load	Mesh Range
0~10V Adapter	100-240	4.55A	15m
12V 0~10V Adapter	12 AC/DC	-	15m
LED Stripe Adapter (2A/CH)	12/24 DC	2A/CH	15m
LED Stripe Adapter (10A/CH)	12/24 DC	10A/CH	15m
Outdoor Relay	12 AC/DC	12.5A	15m





電源ユニット	Voltage(V)	Power(W)	Mesh Range
BT Driver 1CH	100-240	40	15m
BT Driver 2CH	100-240	40	15m



リピータ	Voltage(V)	Power(W)	Mesh Range
Indoor Repeater	5 DC	0.5	50m
Outdoor Repeater	12 AC/DC	0.5	50m
Dali Repeater	100-240	0.5	50m



ゲートウェイ	Voltage(V)	Power(W)	Mesh Range	Wi-Fi Range
IP Camera A80	100-240	16	30-50m	10m
IP Camera Downlight	100-240	16	30-50m	10m
GATEWAY Desk Type	5 DC	2.5	30-50m	10m
GATEWAY Wire Type	12 AC/DC	<2	30-50m	10m
Wi-Fi IP Camera+Gateway	100-240	<2	30-50m	10m



LEDランプ	Voltage(V)	Power(W)	Total Flux(lm)	CRI	Mesh Range	Colors
G45	100-240	4.5	350	80	15-20m	
B35	100-240	4.5	350	80	15-20m	
A60	100-240	8	810	80	15-20m	
A70	100-240	10	1050	80	15-20m	
B35-Filament	100-120 200-240	4	350	80	15-20m	
A60-Filament	100-120 200-240	4	350	80	15-20m	
G95-Filament	100-120 200-240	4	350	80	15-20m	
ST64-Filament	100-120 200-240	4	350	80	15-20m	
MR16	12 AC/DC	5	400	80	15-50m	
PAR16	100-240	5	400	80	15-50m	
PAR38	100-240	15	1100	80	15-20m	
JC Bi-Pin	12 AC/DC	1.7	140	80	15-20m	
GX53-75mm	100-240	6	600	80	15-20m	
GX53-90mm	100-240	8	790	80	15-20m	
GX53-90mm	100-240	10	1100	80	15-20m	
BR30	100-240	10	750	80	15-20m	
BR40	100-240	12	1200	80	15-20m	

LED照明器具	Voltage(V)	Power(W)	Total Flux(lm)	CRI	Mesh Range	Colors
Downlight Adjustable	100-240	8	500	95	15-20m	
Downlight 9cm	100-240	10	940	80	15-20m	
Downlight 15cm	100-240	14	1000	80	15-20m	
Step light 5inch	12 AC/DC	2.5	140	80	15-20m	
Step light 9inch	12 AC/DC	5.5	300	80	15-20m	
T5 Batten 1Ft	100-240	4.5	400	80	15-20m	
T5 Batten 2Ft	100-240	8	800	80	15-20m	
T5 Batten 3Ft	100-240	12.5	1300	80	15-20m	
T5 Batten 4Ft	100-240	17	1700	80	15-20m	

www.bltc.com.tw ®

Beautiful Light,
Beautiful Life.

GET IT ON Google Play

Download on the App Store

No. 17, Machouhouyuanqu 2nd Rd., Lucao Township, Chiayi County 611, Taiwan (R.O.C.) +886-5-362-5177 +886-5-362-5179 sales@bltc.com.tw